

Shaving Mill

MADE IN THE U.S.A

21 YARDS OF SHAVINGS PER HOUR



- Shaves material in both directions
- Thickness of shavings is adjustable
- Produces uniform, thin, curly shavings
- High Volume - Consistency - Dependability



Wood box is manufactured to the highest standards. The open top design allows box to be filled while operating.

HIGH Production Mill!

Model 14009 - 86 HP Diesel, Perkins Engine - Optional Gas Engine, or Electric Motor!

Double Chain & Sprocket Design - Provides Positive Box Feed!

Large Capacity Wood Box - Less Loading Time, More Production Time!

Sensors at Both Ends of the Box - Ensures Safe and Efficient Operation!

15 Hardened Razor Backed Cutter Knives - Sharpenable and Height Adjustable for Longer Life! Approximately 500,000 board feet of operation, in between sharpenings! (Varies depending on material)

Dual Torflex Axles, Extra Large Highway Tires - Easy Transport Between Work Sites. Unit is Also Available as a Stationary Unit!

Delivery, Installation & Instruction - Ensures Safe, Efficient & Positive Results with Quick Return on Investment!



360° Exhaust Chute on Blower Assembly

*Quality of Workmanship, Innovative Design,
Built to Last, Salsco, Inc.*

SALSCO, INC.
LEADER BY DESIGN

SPECIFICATIONS AND OPTIONS - 30" Shaving Mill

Engine	(Electric motors, gas engines and diesel engines are available)
Engine Oil Drain	Engine has an oil drain hose for ease of maintenance.
Frame/Trailer	8", I-Beam construction, all continuous welds, fully gusseted for strength.
Axles	Dual, 7,000 lb. Torflex Axles, with Electric Brakes with break-away switch.
Hitch Coupler	Different sizes and types available to suit tow vehicle. 4 - Position hitch mounting bracket.
Tires & Wheel Assemblies	Qty. 4 - 225/75R15D, Load range D, 8 Ply, Radial.
Fenders & Light Package	Heavy duty, diamond plate fenders, with light enclosures. D.O.T. approved light package; stop, directional, & brakes. 7-Prong commercial type electric plug.
Tongue	3" x 5" X 3/8" wall, rectangular steel tubing, with 4 - position hitch mounting bracket.
Cutter Shaft	Specially designed to cut both directions & remove shavings throughout the cut.
Shaving Knives	15 knives, razor backed, sharpenable, replaceable & adjustable. Made of hardened steel.
Shavings Thickness	Size of shavings can be adjusted several different ways. Change the wires in the blower system, raise or lower either the cutter blades, or the cutter shaft.
Bearings	Heavy duty, cast iron, self-centering, greasable, commercial type.
Pulleys	Cast type with taper lock centers.
Shafts	All adjusting shafts have pusher screws to help keep shafts aligned.
Pumps & Motors	Hydraulic pump is variable speed, piston type. Hydraulic motor , 12.1 C.I.D., commercial type motor.
Hydraulic Valve	Adjustable, with cross over relief.
Hydraulic Hoses	2,500 P.S.I. - working. 10,000 P.S.I. - burst.
Hydraulic Tank	16-3/4" x 8" x 12-1/4". 6-1/2 gallon capacity, drain plug & cushioned.
Wood Box	Steel, completely re-enforced with 4" x 1-1/2" steel channel beams on all sides. Extra large 30" wide, by 8' 6" long, x 30" deep. 1/4" and 1/2" steel plate walls. Steel wheels are mounted on all four corners. Open box design, can be filled while operating.
Debris Fingers	Keep slab slivers inside box.
Sensors	Qty. 2 - These sensors prevent the box from over travel.
Wheel Tracks	Wood box steel wheels ride on 2" x 2" x 1/4" angle, welded to 1/2" plate, welded to deck plate. Top and bottom wheel tracks keep the wood box from raising up during operation.
Auto Reverse Switch	Unit is equipped with auto reverse to keep the box moving back and forth over the cutter head, without an operator.
Deck Plate	3/4" Thick steel plate.
Chains	All chains are extra heavy duty.
Grease Fittings	All grease fittings have remote grease blocks for ease of maintenance.
Stabilizer Stands	Stationary legs, constructed of 1/4" thick steel plate and steel tube.
Guards & Safety Decals	All moving parts, chains, sprockets, etc. are guarded and safety decals are in place.
Exhaust/Blower	Heavy duty, 360° directional exhaust blower is standard. Wire fingers help break up large shavings when shaving green wood. Blower system can be disabled so that shavings can be dropped down to a conveyor system underneath the machine.
Fuel Tank	36" x 14" x 20". 43.6 gallon capacity. Cushioned, with screw cap and dipstick.
Paint	All parts are individually painted, to prevent rust from building up between parts. Polyester baked, powder coated to resist weathering and ultra violet rays.
Dimensions:	Transport Length - 25', Transport Width - 9' 6", Transport Height - 7' 2", Transport Weight - Approximately 10,000 lbs.

Specifications & options subject to change without notice.

REV 8/04

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawncare, Rental, Construction, Tree care, Wood Processing, Nursery & Farm Industries

Other Salsco Equipment

3-1/2" - 18", Gas, Diesel, and P.T.O, Wood/Brush Chippers

Chipper Shredder Vacuum - Tailgate & Truckloader Vacuums up to 65 HP

Shaving Mills - Gas and Electric Greens Rollers



105 School House Road
Cheshire, CT 06410 U.S.A.
800-872-5726, 203-271-1682, 203-271-2596 (Fax)
sales@salsco.com, www.salsco.com