

Chipper, PTO - 6210XT

10" CAPACITY

MADE IN THE U.S.A



The Model 6210XT, is a 10" capacity chipper with a large 10" x 14" infeed opening. Upper feed roll assembly (pictured below) raises to accommodate branches & limbs up to 10" in diameter. The infeed tray lowers to a full 40" from the feed rolls for the extra safety when feeding the machine. No tools are required to adjust the 360° Exhaust Chute, and Easy Adjust Exhaust Flap to direct chipped material where required. Dual Feed Rolls provide extra crushing power for large amounts of bushy material. Easily accessed from either side, the infinite speed infeed handle has a full reverse, for safety!



Only 35 HP Required @ the PTO!



Nine 1/2" Thick, double-sided, chip blades, segmented into 3-knife pockets. Easy access to blades through 1/4" thick steel impeller housing. 1" thick impeller, with 3-welded and gusseted paddles for better chip discharge and air-flow.



Optional Speed Sensing automatically monitors impeller RPM and stops infeed to allow RPM recovery.



Flow Control Valve provides infinite speed control to accommodate all tractors.

4-Bolt, cast iron, self aligning, greasable bearings! Replaceable, Sharpenable, Adjustable steel bed knife!



Quality of Workmanship, Innovative Design, Built to Last!

Salsco, INC.
LEADER BY DESIGN

SPECIFICATIONS AND OPTIONS - MODEL 6210XT PTO GRAVITY FEED WOOD CHIPPER

- INFEEED CHUTE:** 30" High x 31 Wide" opening at the infeed handle. Fold down infeed tray extends to 40" to infeed rolls.
- INFEEED OPENING:** 14" Wide x 10" High opening at the infeed rolls, in operating position.
- EXHAUST CHUTE:** 360° Swivel Exhaust, 11 gauge steel, easy adjust exhaust flap, no tools necessary to adjust.
- CHIPPER DISC:** 1" Thick x 29" Diameter, 6 - welded and gusseted exhaust paddles, fully balanced.
- CHIPPER DISC HOUSING:** 7 Gauge thick steel impeller housing is vented to provide more air flow for chip exhaust.
- INFEEED ROLLS:** Quantity - 2. 24" long x 5-1/2" diameter, weighted, replaceable blades, fully welded.
- PTO SHAFT & COVER:** Heavy duty PTO Shaft & Cover, standard equipment.
- HYDRAULIC COMPONENTS:** Hoses-2,500 PSI operating & 10,000 PSI burst. Motor - 23.8 displacement.
- BED KNIFE:** Replaceable, Sharpenable, Adjustable - 1/2" Thick Steel.
- BEARINGS:** Heavy duty, cast iron, greaseable & self centering.
- FRAME:** 7 Gauge steel frame, fully welded and gusseted for strength.
- PAINT:** Orange, Polyester Powder Coat Paint, provides excellent outdoor weatherability & offers protection against ultra violet discoloration.
- OPTIONS:** Speed Sensing.
- DIMENSIONS:** Length - 94" (Infeed Tray in Up Position), Width - 61"
Height to top of discharge - 81". Weight - 1965 Lbs.

SPECIFICATIONS & OPTIONS, SUBJECT TO CHANGE WITHOUT NOTICE - 1/05

REV. 8/06

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawncare, Rental, Construction, Tree care, Wood Processing, Nursery & Farm Industries

Other Salsco Equipment

**3-1/2" - 18", Gas, Diesel, and P.T.O, Wood/Brush Chippers
Chipper Shredder Vacuum - Tailgate & Truckloader Vacuums up to 65 HP
Shaving Mills - Gas and Electric Greens Rollers**



105 School House Road
Cheshire, CT 06410 U.S.A.
800-872-5726, 203-271-1682, 203-271-2596 (Fax)
sales@salsco.com, www.salsco.com