

Chipper, PTO - 627XT

6" CAPACITY

MADE IN THE U.S.A



The Model 627XT, is a 6" capacity chipper with a large 12" x 8" infeed opening. This unit utilizes, 1/2" Thick x 4" Long, x 4" Wide, Double Edge, chip blades and a 1/2" thick,




reversible, sharpenable, and replaceable bed knife, for consistent chip size and chipping capabilities of even those small, viney, stringy, messy jobs! 360° Exhaust Chute, and Easy Adjust Exhaust Flap. No tools are required to adjust either one. Dual infeed rolls, and adjustable infeed speed help to prevent cloggin & wrapping. Bolted swing away infeed allows easy access to feed rolls.

Only 25 HP Required @ the PTO!



12" x 8" infeed opening to Dual Infeed Rolls. Extra wide Fold Down Infeed Pan, 75" from infeed rolls. Infeed Handle is easily accessible from either side of unit. Reverse, Neutral, Slow and Fast Speed.

Optional Speed Sensing automatically monitors impeller RPM and stops infeed to allow RPM recovery.



Flow Control Valve provides infinite speed control to accommodate all tractors.

6 - 1/2" thick, Double-Sided, Chip Blades, segmented into 3 knife pockets. Easy access to blades through 1/4" thick steel impeller housing. 1" thick X 29" diameter, fully balanced impeller, with 6 welded and gusseted paddles for better chip discharge and air-flow. 4-Bolt, cast iron, self-aligning, greasable bearings! Replaceable, Sharpenable, Adjustable steel bed knife!



Quality of Workmanship, Innovative Design, Built to Last!

Salsco, INC.
LEADER BY DESIGN

SPECIFICATIONS - MODEL 627XT

- INFEED CHUTE:** 24" x 29" Opening at the infeed handle.
- INFEED OPENING:** 12" x 8" Opening at the infeed rolls
- EXHAUST CHUTE:** 360° Swivel Exhaust, 11 gauge steel, no tools necessary to adjust
- CHIPPER DISC:** 1" Thick x 29" Diameter, 6 - welded and gusseted exhaust paddles, fully balanced.
- CHIPPER DISC HOUSING:** 7 Gauge Thick Steel Impeller Housing is Vented to Provide More Air Flow for Chip exhaust.
- INFEED ROLLS:** Quantity - 2. 12" long x 5-1/2" diameter, weighted, replaceable blades, fully welded.
- PTO SHAFT & COVER:** Heavy duty PTO Shaft & Cover, standard equipment.
- HYDRAULIC COMPONENTS:** Hoses-2,500 PSI Operatng & 10,000 PSI burst. Motor - 23.8 displacement.
- BED KNIFE:** Replaceable, Sharpenable, Adjustable - 1/2" Thick Steel.
- BEARINGS:** Heavy Duty, Cast Iron, Greaseable & Self Centering.
- FRAME:** 7 Gauge Steel Frame, Fully welded and gusseted for strength.
- PAINT:** Orange, Polyester Powder Coat Paint, provides excellent outdoor weatherability & offers protection against ultra violet discoloration.
- OPTIONS:** Speed Sensing.
- DIMENSIONS:** Length - 64", Width - 64" Height to top of discharge - 86". Weight - 955 Lbs.

SPECIFICATIONS & OPTIONS, SUBJECT TO CHANGE WITHOUT NOTICE - 7/06

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawncare, Rental, Construction, Tree care, Wood Processing, Nursery & Farm Industries

Other Salsco Equipment

3-1/2" - 18", Gas, Diesel, and P.T.O, Wood/Brush Chippers

Chipper Shredder Vacuum - Tailgate & Truckloader Vacuums up to 65 HP

Shaving Mills - Gas and Electric Greens Rollers



105 School House Road
Cheshire, CT 06410 U.S.A.
800-872-5726, 203-271-1682, 203-271-2596 (Fax)
sales@salsco.com, www.salsco.com