

Chipper-813XT

MADE IN THE U.S.A

13" CAPACITY - DUAL FEED ROLLS

STANDARD FEATURES

- Bottom Feed Roll
- Live Hydraulics
- Feed Sensing with Auto Reverse
- Hydraulic Feed Roll Lift with Down Pressure
- 9,000 lb. Heavy Duty Jack
- Safety light Package
- Adjustable Height Exhaust Chute
- 360° Hand Crank Exhaust Chute
- Easy Adjust Exhaust Flap



STANDARD - 13" High x 18" Wide Extra Large Infeed Opening

Feeding & Chipping beyond all others!



Double Feed Roll - STANDARD
Infeed Debris Grate - OPTIONAL



OPTIONAL - Hydraulic Winch, 9,000# Horizontal Pull

Quality of Workmanship, Innovative Design, Built to Last!

Salsco, INC.
LEADER BY DESIGN

SPECIFICATIONS AND OPTIONS - MODEL 813XT, 13" X 18" WOOD/BRUSH CHIPPER

TOWING HITCH: 2 5/16" ball, or 3" pintle, adjustable for height.

TONGUE: 3" x 6" x 1/4" wall, rectangular steel tube. Bolt on tongue bracket is 1/2" steel plate with 1/4" gussets welded for extra support.

TONGUE JACK: 9,000 lb. capacity, heavy duty jack.

TRAILER: 2" x 6" rectangular tubing with support gussets and continuous welds for strength.

FENDERS: Extra heavy duty 1/4" diamond plate fenders with safety light guards.

LIGHTS: License plate, stop, directional and safety, 7- prong adaptor. D.O.T. approved. Safety Light Package over Infeed Chute.

SAFETY CHAINS: Two (2) 3/8" links x 30" length with slip hooks. Meets SAE safety standards.

AXLE: 7,000 lb Torflex Axle, features an independent suspension, cushioned with rubber, providing a smooth, quiet ride with no transfer of road shock from one wheel to the other. Electric Brakes with break-away switch.

TIRES & WHEEL ASSEMBLIES: 12.0 x 16.5, 10 ply.

PAINT: Orange, polyester powder coated paint offers excellent weatherability and protection against ultra violet discoloration.

FUEL TANK: 25 Gal. 19 1/4" x 12" x 24", with lockable filler cap, sight gauge, and shock mounted with rubber cushions on all mounting brackets.

HYDRAULIC TANK: Triangular. 16 3/4 gal. 24" high - 18" sides (1,881 sq. in.). Lockable filler cap with sight gauge and shock mounted with rubber cushions on all mounting brackets.

INFEED CHUTE: Extra wide profile, 1/4" thick steel plate sides, 57" x 33". 45" from edge of standard infeed tray to center of feed roller for safety. Control bar positioned at top and side of infeed tray to control movement of material - forward/neutral/reverse.

CHIPPER DISC: 2" thick x 40" diameter disc, machined and balanced, mounted on a 4 1/2" diameter steel hub with 6 exhaust blades. (Approximately 700 lbs.)

CHIPPER BEARINGS: 3" - 4 bolt flange bearing. Self centering, heavy duty cast iron type.

CHIPPER BLADES: Six (6) 7 1/4" x 4" x 1/2", double sided, reversible, bolted, and set into 2 knife pockets machined into disc.

INFEED OPENING: 13" x 18" opening at the infeed roll.

BED KNIVES: Two (2) 1- Horizontal, 1" thick x 6 1/4" x 15 3/8" and 1-Vertical, 1" thick x 7 5/8" x 12 15/16". Both knives are reversible and adjustable.

SPEED SENSING: Speed sensing with auto reverse.

HYDRAULIC LIFT CYLINDERS: 2 - Feed roll lift cylinders with down pressure.

LIVE HYDRAULICS: Live hydraulics with remote mount pump.

HYDRAULIC FEED SYSTEM: Heavy duty 800 lb., weighted box type feed system. Feed rate, 0 - 130' per minute. Hydraulic hoses - 2,500 lbs., P.S.I. working, 10,000 lbs. P.S.I. burst, including hydraulic pump, control valve with relief valve, hydraulic motor and 16 3/4 gal. hydraulic oil reservoir. Live hydraulics, speed sensing and hydraulic feed roll lift.

HYDRAULIC FEED ROLLS: 2 - Upper, 21" Diameter x 18" Long. Lower, 14-3/4" Diameter x 17-1/4" Long. Both with replaceable knife blades or teeth, and scraper bars to prevent wrapping.

BATTERY: 12 V automotive style, 900 cold cranks with lockable box.

TOOL BOX: Lockable tool box. 7" W x 16 3/4" L x 6" H.

DISCHARGE: Height adjustable 360° hand crank, swivel chute with easy adjust chip deflector. No tools required for adjustment. (270° stop available, if required)

OVERALL DIMENSIONS: Total length - 171". Width - 80 1/2". Height to top of discharge - 93". Weight - 7,500 lbs. (approximately)

OPTIONS

Spare tire mount	Swing arm mount for warning light
Spare tire and rim	Cone holder on tongue
Castor wheel for 9,000 lb. jack	Chock holders on fenders
Single rear jack stand	Shut-off valve for fuel tank
Mud Flaps	Hydraulic winch, 9,000 # horiz. pull
7-prong socket, tow vehicle	Fluid coupler
6-prong electric plug	Variable speed flow control
6-prong socket, tow vehicle	8,000 lb. T-Flex axle
Brake control box, tow vehicle	Hydraulic swivel tongue
Tool kit to change knives	Fold down infeed tray
Bastard file, knife touch up	Telescoping tongue
Locks with keyed alike keys	Discharge swivel stop
Flashing amber warning light	Discharge infeed grate
Amber strobe light kit	Custom powder coat paint

ENGINE OPTIONS - GASOLINE

FORD, LRG425, - 70 HP

FORD, CSG649, - 95 HP

ENGINE OPTIONS - DIESEL

JOHN DEERE, 4045D, - 80 HP

JOHN DEERE, 4045T, - 115 HP

CATERPILLAR, 3054NA, 83HP

CATERPILLAR, 3054DIT, 127HP

DEUTZ, BF4M1011E, - 83 HP

REV. 8/05

Specifications & Options Subject to Change without Notice.

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawn care, Rental, Construction, Tree care, Wood Processing, Nursery & Farm Industries

Other Salsco Equipment

3-1/2" - 18", Gas, Diesel, and P.T.O, Wood/Brush Chippers

Chipper Shredder Vacuum - Tailgate & Truckloader Vacuums up to 65 HP

Shaving Mills - Gas and Electric Greens Rollers



105 School House Road

Cheshire, CT 06410 U.S.A.

800-872-5726, 203-271-1682, 203-271-2596 (Fax)

sales@salsco.com, www.salsco.com