

Chipper-84 Series

4" CAPACITY

MADE IN THE U.S.A



STANDARD FEATURES

- * Heavy Duty Fenders with Light Enclosures
- * Full Light Package
- * Heavy Duty Tubular Steel Frame
- * 360° Swivel Exhaust
- * T-Flex Axle

Chipper disc is 18-7/8" in diameter and 3/4" thick, with six exhaust paddles, welded and gusseted for extra strength. There are 2 chip blades, 1/2" thick x 7-1/4" long x 4" wide and they are double sided!

Best Performing 4" Chipper on the market!



Optional Feed Sensing.

This option counts the impeller R.P.M. and if the engine is getting loaded up due to a combination of large long logs and not enough horsepower, the Feed Sensing will stop the feed roll and allow the engine to catch up.



The extra wide, 4" high x 8" wide, infeed hopper allows the bushy branches to be pulled in and chipped. This lessens the amount of pruning that needs to be done. Control handle has a slow speed, fast

speed, neutral and reverse to control chip size and feed speed, and is easily accessible from either side of the infeed.

Quality of Workmanship, Innovative Design, Built to Last!

Saisco, INC.
LEADER BY DESIGN

SPECIFICATIONS - MODEL 8416K, 8416B, 8420K, 8425K, WOOD/BRUSH CHIPPERS

HYDRAULIC TANK:	10" x 8-1/4" x 8" steel tank. 2.6 gallon capacity, with lockable filler cap with dip stick.
INFEED CHUTE:	29" wide x 24" high, (689 sq. in.) 26-7/8" from edge to roll, 28" from ground to tray. Control bar positioned at top of infeed tray to control movement of the feed wheel. High speed, low speed, neutral & reverse.
CHIPPER DISC:	3/4" thick x 18-7/8" diameter disc mounted on a 1" diameter steel shaft with six exhaust blades. Approximately 160 lbs.
CHIPPER BLADES:	Two chip blades. Each blade is 7-1/4" long x 4" wide x 1/2" thick, oil hardened steel. Double sided.
CHIPPER DISC HOUSING:	1/4" thick, steel plate, vented, chipper disc housing.
INFEED OPENING:	4" x 8" opening at the infeed roll. Less trimming and pruning.
BED KNIVES:	(2) One horizontal and one vertical. Both are adjustable, reversible and 1" thick steel.
BEARINGS:	Heavy Duty, Cast Iron, greasable and self centering.
HYDRAULICS:	Piston type hydrostatic pump with variable speed control, Char-Lynn drive motor. Hydraulic hoses - 2,500 lbs., P.S.I. working, 10,000 lbs. P.S.I. burst.
FEED ROLL:	One 7" diameter x 8" long feed roll, with cutter blades, powered by a variable speed hydraulic pump.
FRAME:	1-1/2" X 2" X 1/8" Wall, Rectangular Steel Tube, with cross beam for extra strength.
T-FLEX AXLE:	1800 lbs. Capacity Torsion axle
BATTERY:	12 Volt, Automotive Style
TONGUE:	2" x 3" x 1/4" Wall, Rectangular Steel Tube, 2" Ball Coupler, with Safety Chains, 2,000 lb. Capacity Top-Wind Jack, 10" Lift.
PAINT:	Orange, polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultra violet discoloration.
OPTIONS:	Speed Sensing 20 HP Kohler Engine (Model 8420K) 25 HP Kohler Engine (Model 8425K)
DIMENSIONS:	Length: 7' 3" Width: 5' Height to top of discharge - 5' 8" Weight - 1200 lbs. (approximately)

Specifications & options subject to change without notice.

REV. 7/03

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawn care, Rental, Construction, Tree care, Wood Processing, Nursery & Farm Industries

Other Salsco Equipment

3-1/2" - 18", Gas, Diesel, and P.T.O, Wood/Brush Chippers

Chipper Shredder Vacuum - Tailgate & Truckloader Vacuums up to 65 HP

Shaving Mills - Gas and Electric Greens Rollers



105 School House Road
Cheshire, CT 06410 U.S.A.
800-872-5726, 203-271-1682, 203-271-2596 (Fax)
sales@salsco.com, www.salsco.com