

Chipper-86 Series

MADE IN THE U.S.A

6" CAPACITY - GAS OR DIESEL



Pictured is the Model 8635 with a 35 HP Kubota, Diesel Engine

Extra Wide 12" Infeed Opening!

Feed directional control bar (slow speed, fast speed, neutral and reverse) is conveniently mounted at top and sides of the infeed hopper and is *easily accessed and operated from any position*. *360° exhaust chute* and chip deflector are easily adjusted without tools. *Centrifugal clutch* provides easy and dependable start. Speed sensing, which monitors the impeller R.P.M. is optional.



1/2" thick, double sided chip blades are easily accessed for replacement and maintenance. *1" thick x 26" diameter impeller, with 6 fan blades* to exhaust material.

Quality of Workmanship, Innovative Design, Built to Last!

Salsco, INC.
LEADER BY DESIGN

MODELS 8625, & 8635, STANDARD FEATURES, SPECIFICATIONS & OPTIONS

TOWING HITCH:	Adjustable height hitch. 2" ball, 2 5/16" ball, or 3" pintle couplers available.
TONGUE:	2" x 3" x 1/4" wall, rectangular steel tube. Bolt on tongue bracket is 1/2" steel plate bracket with 1/4" gussets.
TONGUE JACK:	Top wind swivel snap ring mount jack. 1,000 lb. lift capacity. Lift-10". Secures in either an up or down position.
TRAILER:	3" x 2" x 1/4" wall rectangular steel tube, continuous welds for strength and gusseted where needed.
FENDERS:	1/4" heavy duty diamond plate fenders with safety light guards.
LIGHTS:	Stop, directional and safety. Enclosed
SAFETY CHAINS:	3/16" diameter x 48" long, with 3/8" diameter hooks. Meets SAE safety standards.
AXLE:	2,400 lb. Torflex Axle, features an independent suspension, cushioned with rubber, providing a smooth, quiet ride with no transfer of road shock from one wheel to the other.
TIRES:	(2) F-78-14. Load range C/6 ply rating. High speed, highway rib mounted on a five bolt white spoked wheel.
PAINT:	Orange, polyester powder coated paint provides excellent outdoor weatherability and offers protection against ultra violet discoloration.
FUEL TANK:	10 1/4" x 13" x 22" steel tank. 13 gallon capacity with lockable filler cap, dip stick & drain plug.
HYDRAULIC TANK:	8 1/4" x 10 3/8" x 10 1/4" steel tank. 4 gallon capacity, with lockable filler cap, dip stick & drain plug.
INFEED CHUTE:	40" wide x 23" high, (920 sq. in.) 61" from edge to pinch point, 19 3/4" from ground to tray. Fold down infeed pan with sides. Control bar positioned at top of chute to control movement of the feed wheel - forward/neutral/reverse.
CHIPPER DISC:	1" thick x 26" diameter disc mounted on a 2" diameter steel shaft with four exhaust blades. (Approximately 200 lbs.)
BLADES:	Two sets of chip blades, 2 blades per set. Each blade is 5" long x 4" wide x 1/2" thick, oil hardened steel, and double sided.
INFEED OPENING:	6" x 12" opening at the infeed roll.
BED KNIVES:	(2) One horizontal and one vertical, Both are adjustable and 1" thick steel.
HYD. FEED SYSTEM:	Sunstrand BDP10 piston type hydrostatic pump with variable speed control. Maximum feed rate, 94' per minute. Hydraulic hoses - 2,500 lbs., P.S.I. working, 10,000 lbs. P.S.I. burst.
FEED ROLL:	One 7" diameter x 12" long feed roll, with cutter blades. Blades for soft or hard wood, powered by a hydraulic motor.
BATTERY:	12 V automotive style, 350 cold cranks with lockable box.
TOOL BOX:	Lockable tool box and it's large enough to hold a grease gun and other necessary tools.
DISCHARGE:	360 ° swivel chute with adjustable chip deflector. No tools necessary for adjustment.
DIMENSIONS:	Length with feed tray closed - 109". Width - 78". Height to top of discharge - 90". Weight - 2,120 lbs. (approximately)
ENGINE OPTIONS:	25 hp Kohler O.H.V., Gas 35 hp Kubota, DIESEL
OPTIONS:	Speed Sensing. 3" Pintle, 2" Ball, 2 -5/16 " Ball (Extra). Spare tire and rim. Custom Paint

Specifications & Options subject to change without notice.

REV. 8/05

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawncare, Rental, Construction, Tree care, Wood Processing, Nursery & Farm Industries

Other Salsco Equipment

3-1/2" - 18", Gas, Diesel, and P.T.O, Wood/Brush Chippers

Chipper Shredder Vacuum - Tailgate & Truckloader Vacuums up to 65 HP

Shaving Mills - Gas and Electric Greens Rollers



105 School House Road
Cheshire, CT 06410 U.S.A.
800-872-5726, 203-271-1682, 203-271-2596 (Fax)
sales@salsco.com, www.salsco.com