

3" CAPACITY COMPARISON

Manufacturer	Salsco	Salsco	Wallenstein
Model	600PTO	624PTO	BX 32s
Capacity	3" Rd. wood cap. (max 4 1/4" slab)	3" Rd.wood cap. (max 5" slab)	3"
HP Requirements	PTO Driven, 8HP minimum required at the PTO. Gravity Feed	PTO Driven, 16HP minimum required at the PTO. Gravity Feed	PTO Driven 12HP TO 30 HP required, Self feeding hopper
Infeed Opening	4-1/4"H X 3-12"W	4"H X 5"W	3" X 6"
Impeller Housing	7 gauge thick steel, continuous welds.	7 gauge thick steel. Impeller housing is vented to provide more air flow for chip exhaust.	Specifications not available
Impeller	1" thick X 13" dia. Fully balanced, 4 exhaust paddles, welded & gusseted. 40 lbs.	3/4" thick X 22-1/4" dia. Fully balanced, 4 exhaust paddles, welded & gusseted. 117 lbs.	17" Rotor 45 LBS.
Chipper Knives	(2) 3/8" thick x 4-1/2" long.	(2) 1/2" thick x 7" long, double-sided.	2 offset knives
Bed Knives	(1) Replaceable, sharpenable, adjustable - 1/2" thick steel.	(1) Replaceable, sharpenable, adjustable - 1/2" thick steel.	1 bed knife
Exhaust Chute	7 gauge steel, with exhaust deflector will channel exhaust into a 30 gallon debris container if needed.	360 degree swivel chute with adjustable chip deflector. No tools required for adjustment.	58" Discharge hood height
Hitch	3 point hitch	3 point hitch. iMatch bracket available.	3 point hitch mount iMatch & quick hitch compatible
Options			
Dimensions	46" X 28" X 47"	55" X 48" X 70"	32" X 32" X 65"
Weight	388 LBS.	525 LBS.	320 LBS.
Warranty	1 Year	1 Year	1 Year