

# CHIPPER

## Model 6210XT, PTO

**Salsco, INC.**  
LEADER BY DESIGN



The Model 6210XT, PTO is a **10" capacity hydraulic feed chipper** with a large **10" x 14" infeed opening**. Upper feed roll assembly (pictured below) raises to accommodate branches & limbs up to 10" in diameter. The infeed tray lowers to a full 40" distance from the feed rolls for extra safety when feeding the machine. No tools are required to adjust the 360° exhaust chute and the easy adjust exhaust flap to direct chipped material where required. **Dual feed rolls** provide extra crushing power for large amounts of brushy material. Easily accessed from either side of the infeed, the infinite speed infeed handle



has a full reverse, for safety! Heavy duty slip clutch drive shaft complete with shield is standard, and is **rated for 65HP@540 RPM**.

## Only 35HP Required @ the PTO!

Nine **(9) 1/2" thick, double-sided, chip blades**, segmented into (3) knife pockets. Easy access to blades through 1/2" thick vented steel impeller housing. **410 lb., 1" thick x 42" diameter impeller**, with (3) welded and gusseted paddles for better chip discharge and air-flow.



4 Bolt, cast iron, self aligning, greaseable bearings! Replaceable, sharpenable, adjustable steel bed knife!



**Optional Speed Sensing** monitors impeller RPM and stops infeed to allow impeller RPM recovery. **540PTO RPM recommended.**



Flow Control Valve (Standard Equipment) provides infinite speed control to accommodate all tractors.

**Salsco, INC.**  
LEADER BY DESIGN

*Quality of Workmanship, Innovative Design, Built to Last!*

<b>SPECIFICATIONS - MODEL 6210XT, PTO CHIPPER</b>	
<b>INFEED OPENING:</b>	10" high x 14" wide infeed opening to dual feed rolls.
<b>INFEED TRAY:</b>	Extra wide, 31" wide x 30" high, with fold down infeed tray. Control bar positioned at top of infeed tray to control movement of the feed roll. High speed, low speed, neutral & reverse.
<b>FRAME:</b>	7 gauge steel frame, fully welded and gusseted for strength.
<b>IMPELLER HOUSING:</b>	7 gauge steel, impeller housing is vented to provide more air flow for chip exhaust.
<b>EXHAUST CHUTE:</b>	360° swivel exhaust chute and exhaust flap are both quickly and easily adjusted to direct exhaust with no tools.
<b>FEED ROLLS:</b>	Two (2), 24" long x 5-1/2" diameter, weighted, replaceable blades, fully welded.
<b>IMPELLER:</b>	Fully balanced, 1" thick x 42" diameter steel impeller with three (3) welded and gusseted exhaust paddles. 410 lbs. (Approximately)
<b>CHIP BLADES:</b>	Nine (9) 1/2" thick x 5-1/8" long x 4" wide, double-sided.
<b>BED KNIFE:</b>	One (1), 1/2" thick steel, replaceable, sharpenable, & adjustable.
<b>DRIVE SHAFT &amp; SHIELD:</b>	Heavy duty slip clutch drive shaft with shield, rated at 65HP @ 540RPM.
<b>HITCH:</b>	3-Point Hitch, Category 1.
<b>BEARINGS:</b>	4-bolt, heavy duty, cast iron, greaseable & self-centering.
<b>HYDRAULIC COMPONENTS:</b>	<b>Hoses</b> - SAE JIC hose ends & fittings. 3,000 P.S.I. working & 12,000 P.S.I. burst. <b>Motor</b> - 23.8 displacement for easy connection to tractor remotes. <b>Flow control</b> is standard.
<b>GUARDS/DECALS:</b>	All moving parts guarded. Full set of safety decals.
<b>PAINT:</b>	Orange, polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultraviolet discoloration. All parts painted separately.
<b>OPTIONS:</b>	Speed Sensing.
<b>DIMENSIONS:</b>	Length: 7' 10"
	Width: 5' 1"
	Height: 6' 9"
	Weight: 1,965 lbs.

Specifications & Options Subject to Change Without Notice

REV. 10-29-2020

#### MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawn care, Rental, Construction, Tree Care, Wood Processing, Nursery & Farm Industries

**3-1/2" - 18" Capacity, Gas, Diesel, & PTO Wood/Brush Chippers - Slab Chippers**  
**Gas, Electric & Tow Behind Rollers - Tranz-Former Roller - CRV Core Recovery Vehicle**  
**Mini-Paver - Mini-Track Paver - Cobra Curbers - Scorpion Router - Concrete Paver**  
**Chipper Shredder Vacuums - Tailgate & Truckloader Vacuums**  
**9 cu. yds. - 50 cu. yds. Per Hour, Electric, PTO & Diesel Powered Shaving Mills**

Salsco, INC.

LEADER BY DESIGN

105 Schoolhouse Road  
Cheshire, CT 06410 U.S.A.  
800-872-5726 (Toll Free), 203-271-1682, 203-271-2596 (Fax)  
[www.salsco.com](http://www.salsco.com), [sales@salsco.com](mailto:sales@salsco.com)