

# GAS ROLLER Models 09067 & 09065

**Salsco, INC.**  
LEADER BY DESIGN



**MADE IN  
THE U.S.A.**



With **two oscillating rolls**, both driven for positive traction and articulating steering, the Models 09067 & 09065 have proven themselves to be invaluable tools at Golf Courses and Clubs everywhere. These Rollers have up to a **40° climbing traction** without slippage or loss of control. The transport trailer comes standard with the roller, equipped with turf tires to protect the turf and an extra-long tailgate with full rubber traction mat and loading guides for easy loading and transport.



## Rolling Greens Since 1992 !

- 8HP Honda Pull Start Engine (09067), 13HP Honda Electric Start Engine (09065)
- 12 Volt Battery (13HP Honda Only)
- Roll Housings Articulate at Different Degrees of Travel, which allows for 100% Roll to Ground Contact
- 36" Rolling Swath
- Ground pressure - 4.2 lbs P.S.I. without water, 5.6 lbs. P.S.I. with water.
- Transport Trailer is Standard
- Options: Rotary Brush System, LED Light Kit, Arm Rest Seat Upgrade, Top Dressing Brush Kit, Spike-Air Kit, Tournament Roll Kit.



Top Dressing Brush Kit

Brushing sand after top-dressing is easily performed with the optional Top Dressing Brush Kit, available on all Greens Rollers. The Top Dressing Brush Kit, used when rolling clay courts, reduces the amount of time before play can begin.



Spike-Air Kit

When using the Spike Air Kit on the green, it will gently spike the green to allow water and oxygen penetration through the crust to the roots of the plant.

The Tournament Roll Kit consists of two smaller diameter rolls, one on each side, which allows for a double roll in one pass, increasing ball speed in 1/2 the time.



Tournament Roll Kit

**Salsco, INC.**  
LEADER BY DESIGN

*Quality of Workmanship, Innovative Design, Built to Last!*

SPECIFICATIONS - Models 09065 & 09067 Gas Rollers	
<b>WARRANTY:</b>	5 - Year Limited Warranty.
<b>ENGINE OPTIONS:</b>	8HP Honda, pull start, 13HP Honda, electric start, rubber mounted to reduce vibration.
<b>FUEL TANK:</b>	Provided with engine. 1.6 gallons.
<b>CONTROLS:</b>	On/Off switch, choke & fuel.
<b>HOUR METER:</b>	Standard.
<b>BATTERY:</b>	12 Volt, 245 CCA automotive type (13HP Honda units).
<b>ENGINE COOLING FAN:</b>	Standard (13HP Honda units).
<b>SEAT:</b>	Molded cushion with protective edge trim, neutral safety switch & forward/reverse adjustment. Rubber mounted to reduce vibration.
<b>STEERING SYSTEM:</b>	Both rolls articulate and oscillate to smooth the surface without changing the undulations designed into the green.
<b>STEERING WHEEL:</b>	13-1/4" diameter, automotive type tilt steering wheel. 13-1 ratio.
<b>MAIN FRAME:</b>	2-1/2" x 2-1/2" x 1/4" steel square tube. Fully gusseted and continuous welds.
<b>DRIVE ROLLS:</b>	Two (2) - Oscillating steel rolls, both driven for positive traction. 1-1/4" roll mounting bearing. 10-3/4" diameter, 36" long with beveled ends & scrapers. Rolls are machined to within two thousandths of an inch concentricity.
<b>TRACTION DRIVE:</b>	Hydraulic pump to 2 hydrostatic - 1 to each roll. Chain drive from hydraulic motors to rolls. #50 Chain & Sprockets.
<b>CLIMBING TRACTION:</b>	Up to 40°.
<b>BRAKES:</b>	Hydrostatic.
<b>HYDRAULIC COMPONENTS:</b>	<b>Hoses:</b> SAE JIC hose ends & fittings. 3,000 P.S.I. working & 12,000 P.S.I. burst. <b>Motors:</b> Two (2) Char-Lynn 7.3 cubic inch displacement. <b>Pump:</b> One (1) Piston type, .62 cubic inch displacement.
<b>ROLLING SWATH:</b>	36"
<b>SPEED:</b>	Variable, 0 - 5.4 MPH
<b>GROUND PRESSURE:</b>	4.2 lbs. P.S.I. without water, 5.6 lbs. P.S.I. with water.
<b>TRANSPORT TRAILER:</b>	<b>Axle:</b> Spindle type with greaseable hub assemblies. <b>Tire/wheel assemblies:</b> 18.5 X 8.5-8 load range "C", 6 ply, rated 935 lbs. <b>Hitch:</b> Tractor type hitch. <b>Jack:</b> 500 lbs. side crank with swivel wheel. Full rubber mat in box and on tailgate.
<b>GUARDS/DECALS:</b>	All moving parts guarded. Full set of safety decals.
<b>PAINT:</b>	Orange, polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultraviolet discoloration. All parts painted separately.
<b>ROLLER OPTIONS:</b>	Rotary Brush System, LED Light Kit, Top Dressing Brush Kit, Spike-Air Kit, Tournament Roll Kit, Arm Rest Seat Upgrade.
<b>ROLLER DIMENSIONS:</b>	Length: 3'3" Width: 3'3" Height: 3'9" Weight: 604 lbs.
<b>TRAILER DIMENSIONS:</b>	Length: 3'5" I.D. Width: 3'8" I.D. Side Rails: 10" Hitch Height: 16" Weight: 197 lbs.

Specifications & Options Subject to Change Without Notice

REV. 9-28-2020

## MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawncare, Rental, Construction, Tree Care, Wood Processing, Nursery & Farm Industries

**3-1/2" - 18" Capacity, Gas, Diesel, & PTO Wood/Brush Chippers - Slab Chippers**  
**Gas, Electric & Tow Behind Rollers - Tranz-Former Roller - CRV Core Recovery Vehicle**  
**Mini-Paver - Mini-Track Paver - Cobra Curbers - Scorpion Router - Concrete Paver**  
**Chipper Shredder Vacuums - Tailgate & Truckloader Vacuums**  
**9 cu. yds. - 50 cu. yds. Per Hour, Electric, PTO & Diesel Powered Shaving Mills**

**Salsco, INC.**  
 LEADER BY DESIGN

105 Schoolhouse Road  
 Cheshire, CT 06410 U.S.A.  
 800-872-5726 (Toll Free), 203-271-1682, 203-271-2596 (Fax)  
[www.salsco.com](http://www.salsco.com), [sales@salsco.com](mailto:sales@salsco.com)