GAS ROLLER
Model HP11-III

Salsco, INC.
LEADER BY DESIGN

MADE IN THE U.S.A.

Unit pictured with the optional Top Dressing Brush Kit & LED Light Kit.

Three Driven Rolls that oscillate and articulate guarantee 100% roll to ground contact which assures traction without slipping. The HP11-III travels over the ground following the undulations designed into the turf and smooths the surface without changing it. The almost 11 MPH ground speed and 73" rolling swath makes it a machine that is hard to beat. With 168 sq.in. of contact surface and a weight of 1180 lbs., the P.S.I. is very low, coming in at only 7.0 P.S.I.

73" Rolling Swath!

- 13HP Honda Electric Start Engine
- 12 Volt Battery
- 6 Gallon, CARB Approved Fuel Tank
- Engine Cooling Fan
- Roll Housings Articulate at Different Degrees of Travel, Which Allows for 100% Roll to Ground Contact
- Transport Trailer is Standard
- Options: Cross Contamination Prevention Kit, Top Dressing Brush Kit, LED Light Kit, Arm Rest Seat & Pedal Extensions

Unit pictured with the optional Cross Contamination Prevention Kit.

The Transport Trailer is equipped with a dual lock latch split tailgate ramp with a full 1/4" thick traction mat on both the trailer box and tailgate with loading guides and a spindle type axle with hub assemblies.

SPECIFICATIONS AND OPTIONS - MODEL HP11-III GAS ROLLER	
WARRANTY:	5 Year Limited Warranty
ENGINE:	13HP Honda, electric start, rubber mounted to reduce vibration
FUEL TANK:	6 gallon CARB approved fuel tank
CONTROLS:	On/Off switch, choke & fuel
HOUR METER:	Standard
BATTERY:	12 Volt, 300 CCA, automotive type
ENGINE COOLING FAN:	Standard
SEAT:	Molded cushion with protective edge trim, neutral safety switch & forward/reverse slide adjustment. Rubber mounted to reduce vibration.
STEERING SYSTEM:	All three (3) roll housings articulate at different degrees of travel, which allows turning without bruising.
STEERING WHEEL:	13-1/4" diameter, automotive type, tilt steering wheel. Hydraulic.
MAIN FRAME:	2-1/2" x 2-1/2" x 1/8" steel square tube. Fully gusseted with continuous welds.
DRIVE ROLLS:	Three (3) oscillating steel rollers, driven for positive traction. One (1) - 10-3/4" diameter x 36" long, two (2) - 10-3/4" diameter x 24" long with beveled ends. All rolls machined to within two thousandths of an inch concentricity.
TRACTION DRIVE:	Traction drive is accomplished by having all three rolls drive and float independently which allows for 100% roll to ground contact.
CLIMBING TRACTION:	Up to 40°
BRAKES:	Hydrostatic drive.
HYDRAULIC COMPONENTS:	One (1) heavy duty variable speed piston pump delivers oil to three (3) hydraulic motors that drive the rolls. **Hoses:** SAE JIC hose ends & fittings. 3,000 P.S.I. working, 12,000 P.S.I. burst. **Motors:** Three (3), one on each roll. **Pump:** One (1) Hydro-Gear 0.97 cubic inch displacement.
ROLLING SWATH:	73"
SPEED:	Variable, 0 - 11 MPH
GROUND PRESSURE:	7.0 P.S.I. without water, 9.2 P.S.I. with water
TRANSPORT TRAILER:	Dual lock latch split tailgate ramp with a full 1/4" thick traction mat on both the trailer box and tailgate with loading guides. **Axle:** Spindle type, with hub assemblies. **Tire/Wheel assemblies:** Two (2) 18.5 x 8.5-8, 6 ply. **Hitch:** Farm type pin coupler, height adjustable. **Jack:** Bolt on, swivel jack stand with caster wheel.
TRANSPORT TRAILER OPTION:	Deflector Step helps prevent damage to the tires when the operator accidentally runs into an obstacle while towing the trailer.
GUARDS/DECALS:	All moving parts guarded. Full set of safety decals.
PAINT:	**Roller:** Orange, **Trailer:** Black. Polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultraviolet discoloration. All parts painted separately.
ROLLER OPTIONS:	Cross Contamination Prevention Kit, Top Dressing Brush Kit, LED Light Kit, Arm Rest Seat, Pedal Extensions.
ROLLER DIMENSIONS:	Length: 5' Width: 6'5" Height: 5'5" Weight: 1180 lbs.
TRAILER DIMENSIONS:	Length: 5'8" Width: 6'7" Height: 4'1" Weight: 510 lbs.

Specifications & Options Subject to Change Without Notice **Rev. 9/10/2021**

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawncare, Rental, Construction, Tree Care, Wood Processing, Nursery & Farm Industries

3-1/2" - 18" Capacity, Gas, Diesel, & PTO Wood/Brush Chippers - Slab Chippers
Gas, Electric & Tow Behind Rollers - Tranz-Former Roller - CRV Core Recovery Vehicle
Mini-Paver - Mini-Track Paver - Cobra Curbers - Scorpion Router - Concrete Paver
Chipper Shredder Vacuums - Tailgate & Truckloader Vacuums
9 cu. yds. - 50 cu. yds. Per Hour, Electric, PTO & Diesel Powered Shaving Mills

Salsco, INC.
LEADER BY DESIGN

105 Schoolhouse Road
Cheshire, CT 06410 U.S.A.
800-872-5726 (Toll Free), 203-271-1682, 203-271-2596 (Fax)
www.salsco.com, sales@salsco.com