

# Mini-Track Paver-411

*Quality of Workmanship, Innovative Design, Built to Last!*

**MADE IN THE U.S.A.**

THE GO-ANYWHERE PAVER!  
SIDEWALKS,- CART PATHS - TRENCHES, ETC.

- \* LABOR SAVING,
- \* TIME SAVING,
- \* MONEY SAVING!



Hydraulic Tilt Hopper. Hopper easily bolts together. Raise the complete hopper for ease of maintenance.



Extra Large Cut Off Door with two (2) Cylinders & Flow Regulators that open the door evenly & smoothly.



Lifting Rings allow the operator to lift the unit around obstructions while in the field, if necessary.



Hydraulic End-Gates move in & out, and have rulers on the top of the end gate to see where they are.



Hydraulic Moveable Tracks. Available as an option.



All controls are on the rear of the machine, including the Key Switch & Throttle.



Two (2) 9" Cast Augers are independently operated both Forward & Reverse.

*Quality of Workmanship, Innovative Design, Built to Last!*

**Salsco, INC.**  
LEADER BY DESIGN

## SPECIFICATIONS - MODEL 05022 MINI-TRACK ASPHALT PAVER, TP411

<b>ENGINE:</b>	Hatz 14HP Diesel, Model 1D81Z-9221 Electric Start mounted on 1/2" thick steel plate motor mount.
<b>PUMP:</b>	Dual Hydrostatic, Variable Speed. Each section has a displacement of .97 cu. In/rev
<b>DRIVE MOTORS:</b>	Qty. 2 Drive Motors for Tracks - 29.4 Cu.In. Displacement, Eaton Char-Lynn Qty. 2 Drive Motors for Augers - 24.0 Cu.In. Displacement, Eaton Char-Lynn
<b>HOSES:</b>	2,500 P.S.I., working, 10,000 P.S.I., burst
<b>BATTERY:</b>	12 volt, automotive type, 850 CCA
<b>FUEL TANK:</b>	Steel, 8.9 Gallons Capacity
<b>HYDRAULIC TANK:</b>	Steel, 8 Gallon Capacity
<b>HOPPER:</b>	Dual hopper, 1/4" thick, steel plate. Inside hopper tilts to 52° angle for ease of dumping material. 1.85 Sq. Yd. Capacity
<b>SCREED:</b>	4'2" Long x 1'2" Wide, with Crown/Invert Adjustment, Power End Gates and Endgate Adjustment Plates for uniform texture.
<b>AUGER ASSEMBLIES:</b>	(2) 9" Cast Augers, both with independent hydraulic drive, Forward and Reverse
<b>DRIVE:</b>	Hydrostatic; variable forward and reverse
<b>TRACK ASSEMBLIES:</b>	Heavy Duty Bridgestone Tracks. Tracks are self-adjusting, always maintaining the proper adjustment. Track width can be changed from 3' to 4'
<b>CONTROLS:</b>	All controls are located at the rear of the machine over the screed, for ease of operation.
<b>MAIN FRAME:</b>	One (1) piece, 1/4" thick steel main frame. 2" x 2" square tubing supports.
<b>WELDS:</b>	Continuous welds where needed for durability.
<b>GUSSETS:</b>	1/4" gussets where needed for strength.
<b>BEARINGS:</b>	Cast Iron, heavy duty, greaseable.
<b>CHAINS &amp; SPROCKETS:</b>	#80 chain and sprockets.
<b>PAVING SPEED:</b>	0 - 50' +, per minute
<b>PAVING WIDTH:</b>	36" to 72" (Narrow paving with cut off plates)
<b>PAVING THICKNESS:</b>	1/4" - 5" Thick
<b>GUARDS/DECALS:</b>	All Moving Parts Guarded. Full Set of Safety Decals.
<b>PAINT:</b>	Powder coat baked enamel polyester finish; resists ultraviolet light.
<b>DIMENSIONS:</b>	Length: 9' 4" (with step up) Width: 4' 9" Height: 3' 11" (from the ground to the top of hopper) Weight: 3,060 lbs.
<b>WARRANTY:</b>	1-year standard warranty

Specifications & Options Subject to Change Without Notice

REV. 09/2011

### MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawncare, Rental, Construction, Tree Care, Wood Processing, Nursery & Farm Industries

*Other Salsco Equipment*

**Skid Steer Side Dump Bucket - Cobra Curber - Mini Paver - Scorpion Pavement Router  
3-1/2" - 18" Capacity, Gas, Diesel, & P.T.O., Wood/Brush Chippers  
Chipper Shredder Vacuums - Tailgate & Truckloader Vacuums  
Gas and Electric Driven Greens Rollers**



105 School House Road  
Cheshire, CT 06410 U.S.A.  
800-872-5726 (Toll Free), 203-271-1682, 203-271-2596 (Fax)  
[www.salsco.com](http://www.salsco.com), [sales@salsco.com](mailto:sales@salsco.com) (email)