

Manufacturer Model	Salsco 86 Series	Salsco 6235B	Salsco 6235BXT	Wallenstein BTX4224	Wallenstein BXT6224/38	Wallenstein CR 60	Bear Cat CH6670H	Bear Cat CH6614	Bear Cat CH6730H	Brush Bandit 65XP	Rayco RC 6D	Vermeer BC600XL	Carlton 660
Capacity	6" Round Wood 12" slab	6" Round Wood	6" Round Wood	6"	6"	6" (11" Slab max)	6"	6"	6"	6"	6"	6"	6"
Engine Options	Gas: 25 HP Kohler Diesel, 35 HP Kubota 35 HP Yanmar	Gas: 35HP Briggs & Stratton	Gas: 35HP Briggs & Stratton	Honda 24 HP	Honda 24HP Kohler 38HP	Kohler 38HP	Honda 670cc gas or diesel	Honda 614cc	Kohler 730cc	Gas: Kohler 27 HP, Kohler 38HP, KUBOTA 32.5HP, Vanguard 35HP, Wisconsin 35HP Diesel, Caterpillar 28HP & 34HP, Deutz 29.9HP, Kubota 35.1HP, Kubota 44.2HP, Perkins 34HP	Gas: Kohler 25HP, Vanguard 35HP	Kohler Command Pro 27HP	Kohler 27HP
Infeed Opening	6" high x 12" wide	7" x 8" opening to chipper disc	7" x 8" opening to dual infeed rolls.	6-1/2" X 12"	6-1/2" X 12"	7" X 11"	6 1/2" X 13 1/2"	9" X 9"	6.5" X 13.5"	6" X 12"	6" X 6"	6 X 6	6' X 6"
Infeed Tray	40" wide x 23" high, (920 sq. in.) 61" from edge to pinch point, 19-3/4" from ground to tray. Control bar positioned at top of tray to control movement of the feed wheel - (fwd/neutral/rev)	24" x 29" Opening at the outer edge of the infeed tray	24" x 29" Opening at the outer edge of the infeed tray. Control bar positioned at top of tray to control movement of the feed wheel - (fwd/neutral/rev)	Specifications not available	Specifications not available	25" X 34" (hopper)	Specifications not available	Specifications not available	29.2" X 64.82" with drop down feed tray	24" X42" infeed hopper with 30" folding infeed pan	30" X 59" Folding In-feed table	30" X 64"	Folding 10" gauge with 1" tube frame
Hydraulic Feed Roll/Rolls	1 - 7" diameter x 12" long weighted feed roll, with cutter blades, powered by a hydraulic motor.	N/A	2 - 12" long x 5-1/2" diameter, weighted, with replaceable cutter blades, powered by a hydraulic motor.	Gravity feed	Gravity feed	Dual active rollers	Specifications not available	Specifications not available	single 13" diameter with 10 knife blades	Specifications not available	(1) horizontal roll (8" diameter)	One	Top 10 1/2" X 6"
Impeller	1" thick x 26" diameter balanced disc mounted on a 2" diameter steel shaft with four exhaust blades. Approx. 200-lbs.	1" thick x 29" diameter, 6-welded and gusseted exhaust paddles, fully balanced. 210 lbs.	1" thick x 29" diameter, 6-welded and gusseted exhaust paddles, fully balanced. 210 lbs.	30" 197 lbs..	30" 197 lbs.	30" 197 lbs.	26" x 1" 165 lbs.	275 lbs.	26" X 1" 172 lbs.	26" diameter x 3/4" thick	24" disc X 1.25" thick	24" diameter X 1.25" width	26" X 1 1/2"
Impeller Housing	1/4" thick, steel plate wrap, vented to allow for better discharge of processed material. Electric Safety Lock is standard and prevents the engine from being started if the impeller housing is open.	7 Gauge thick steel impeller housing is vented to provide more air flow for chip exhaust.	7 Gauge thick steel impeller housing is vented to provide more air flow for chip exhaust.	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	25" steel face plate	Specifications not available	Specifications not available	Specifications not available	Specifications not available
Chipper Knives	Two sets of chip blades, 2-blades per set. Each blade is 5" long x 4" wide x 1/2" thick, oil hardened steel, and double sided.	6 - 1/2" thick x 4" long x 4" wide, double sided chip blades.	6 - 1/2" thick x 4" long x 4" wide, double sided chip blades.	2 Knives	2 Knives	4 at 197 lbs.	4 Reversible Knives	4 reversible, heat-treated steel chipper blades	4 Reversible Knives	2 pockets (each pocket holds 1) 1/2"X4"X7 1/4" double edged knife)	2	8 Chipper knives	2 knives
Bed Knives	(2) One horizontal and one vertical. Both are adjustable, sharpenable and 1" thick steel.	(1) 1/2" Thick Steel, replaceable, sharpenable & adjustable.	(1) 1/2" Thick Steel, replaceable, sharpenable & adjustable.	Hardened tool steel	Hardened tool steel	Hardened tool steel	Adjustable 4 sided	Adjustable 4 sided	Adjustable 4 sided	4-sided (1/2"X3"X6")	(4 Edge, 3/4" X 5" X 6.6" A8	4	2 1/2" X 6" X 1/2"
Chipper Bearings	Heavy duty, cast iron, greaseable and self centering.	4-Bolt, Heavy Duty, cast iron, greaseable & self centering.	4-Bolt, Heavy Duty, cast iron, greaseable & self centering.	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	4	2" tapered roller
Hydraulic Tank	8-1/4" x 10-3/8" x 10-1/4" steel tank. 4-gallon capacity, with lockable filler cap, dip stick & drain plug.	N/A	3.3 Gallon capacity, lockable steel tank.	Specifications not available	Specifications not available	lockable enclosure for tank	Specifications not available	Specifications not available	6 gallon capacity	7 gallon capacity	7.6 gallon capacity	7 gallon capacity	7 Gallon Capacity High Density Polyethylene rubber mtd.
Hydraulic Feed System	Piston type hydrostatic pump with variable speed control. Maximum feed rate, 94' per minute. Hydraulic hoses - 2,500-lbs., P.S.I. working, 10,000-lbs., P.S.I. burst.	N/A	Hoses - 2,500 PSI Operating & 10,000 PSI burst. (2) Motors - 23.8 displacement, (1) 6 G.P.M. Pump.	Gravity feed	Gravity feed	Electronic feed sensor, hydraulic feed controller unit	live hydraulic feed system	live hydraulic feed system	????	Specifications not available	Specifications not available	Open Center, Return, 10 Micron	

Manufacturer Model	Salsco 86 Series	Salsco 6235B	Salsco 6235BXT	Wallenstein BTX4224	Wallenstein BXT6224/38	Wallenstein CR 60	Bear Cat CH6670H	Bear Cat CH6614	Bear Cat CH6730H	Brush Bandit 65XP	Rayco RC 6D	Vermeer BC600XL	Carlton 660
Exhaust Chute	360-degree swivel exhaust chute and exhaust flap is quickly and easily adjusted to direct exhaust. No tools necessary.	360-degree swivel exhaust, 11 gauge steel, no tools necessary to adjust. Easy adjust exhaust flap.	360-degree swivel exhaust, 11 gauge steel, no tools necessary to adjust. Easy adjust exhaust flap.	88" Discharge Hood Height	88" Discharge Hood Height	360 degree swivel & angle control chute	Standard	8" discharge chute rotates 360 degrees	360 degree rotation 18 positions for locking discharge chute	360 degree manual swivel, with 12" chip deflector	360 degree rotating 94" in height	240 degree angle 94" high	12 gauge adjustable swivel w/ deflector
Fuel Tank	13-Gallon, 10-1/4" x 13" x 22" steel tank. with lockable filler cap, dip stick & drain plug. (8625 - Marine Type, 6 Gallon, Polyethylene tank)	6 gallon, carbon canister fuel tank	6 gallon, carbon canister fuel tank	Specifications not available	Specifications not available	lockable enclosure for tank	Specifications not available	6.5 gallon capacity	9.5 gallon capacity	8 gallon capacity	7.6 Gallon Capacity	7 gallon capacity	6 gallon capacity High Density Polyethylene rubber mtd.
Battery/Batteries	12 V automotive style, 350 cold cranks with lockable box.	12 Volt, 650 cold cranks with lockable box.	12 Volt, 650 cold cranks with lockable box.	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	455	850 CCA 78DT -72
Axle/Axles	2,400-lb. Torflex Axle, features an independent suspension, cushioned with rubber, providing a smooth, quiet ride with no transfer of road shock from one wheel to the other.	2,200-lb. capacity, Torflex Axle	2,200-lb. capacity, Torflex Axle	Specifications not available	Specifications not available	Torflex suspension axle	Specifications not available	Specifications not available	1800 lb. Torsion Suspension Axle	Single 2,000 pound Torflex (gas engines), single 3,500 pound Torflex axle (diesel engines)	2,200# Torsion axle	2000 lb. torsion axle	Dexter Torflex 2,000 pound Cap
Tire/Wheel Assemblies	(2) F-78-14. Load range C/6 ply rating. High speed, highway rib mounted on a five bolt white spoked wheel.	ST205/75R14 Tire & Wheel Assemblies. High speed, highway rib mounted on a five bolt white spoked wheel.	ST205/75R14 Tire & Wheel Assemblies. High speed, highway rib mounted on a five bolt white spoked wheel.	20.5 X 8-10"	20.5 X 8-10"	20.5 X 8-10"	Specifications not available	12" pneumatic tires	P205-75R14	(2) 20.5 X 8 X10" tires (gas engine), (2) P185X14" tires (diesel engines) Rims: 5-bolt white spoke	18.5 X 8 5/8"	18.5 X 8.5 - 8LRC	ST175/80R13 Ld Rng C 1760# @ 50PSI
Tongue	2" x 3" x 1/4" wall, rectangular steel tube. Bolt on tongue bracket is 1/2" steel plate bracket with 1/4" gussets. With safety chains.	2" x 3" x 1/4" wall, rectangular steel tube. Bolt on tongue bracket is 1/2" steel plate bracket with 1/4" gussets. With safety chains.	2" x 3" x 1/4" wall, rectangular steel tube. Bolt on tongue bracket is 1/2" steel plate bracket with 1/4" gussets. With safety chains.	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	3" X 3"	Specifications not available	Telescoping	3" X 3" X 1/4" wall, extension 12"	2" X 3" with 3/16" wall
Hitch	Adjustable Height hitch. 2" ball, 2-5/16" ball, or 3" pintle coupler.	Adjustable Height Hitch, 2" Ball Coupler.	Adjustable Height Hitch, 2" Ball Coupler.	2" Ball & Safety Chains	2" Ball & Safety Chains	2" Ball & Safety Chains	2" ball coupler	2" ball coupler	2" ball coupler	Specifications not available	2" Ball	2" ball coupler	2" coupler
Jack	Top wind swivel snap ring mount jack. 1,000-lb. lift capacity.	Top Wind 2,000 lb. Jack	Top Wind 2,000 lb. Jack	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Adjustable wheel with 850 lb. rating	2,000-lb. "Bulldog" jack	500 lbs. W/caster	Specifications not available	2000# cap screw type swing up
Fenders	1/4" heavy duty diamond plate fenders, stop, directional & safety lights with guards.	1/4" heavy duty diamond plate fenders, stop, direction & safety lights with guards	1/4" heavy duty diamond plate fenders, stop, direction & safety lights with guards	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	10 gauge steel weld on (gas engines), 3/16" heavy duty steel weld on (diesel engines)	Specifications not available	Integrated	12 Gauge
Tool Box	Lockable tool box and it's large enough to hold a grease gun and other necessary tools.	N/A	N/A	Specifications not available	Built in	Built in	N/A	N/A	N/A	N/A	Lockable	Lockable	N/A
Lights	License plate, stop, directional and safety. D.O.T. approved.	License plate, stop, directional and safety. D.O.T. approved.	License plate, stop, directional and safety. D.O.T. approved.	Specifications not available	Specifications not available	Brake & L/R turn signal lights	Specifications not available	Specifications not available	12 volt system LED lights	12 volt system with rubber mounted LED taillights, w/6 prong replaceable coiled trailer power cord.	12V stop, tail, turn, license, side marker	Turning, license, brake tail and side marker	12 Volt
Trailer	3" x 2" x 1/4" wall rectangular steel tube, continuous welds for strength and gusseted where needed.	7 gauge steel frame, fully welded and gusseted for strength.	7 gauge steel frame, fully welded and gusseted for strength.	Mounting system/trailer	Mounting system/trailer	Mounting system/trailer	Road Towable	Road Towable	4" c-channel 7 gauge steel thickness	Specifications not available	Specifications not available	Specifications not available	Frame 2" X 3" with 3/16" wall
Guards/Decals	All safety guards are standard. Full Set of Safety Decals.	All moving parts guarded. Full set of safety decals.	All moving parts guarded. Full set of safety decals.	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	N/A	Specifications not available	Specifications not available	Specification s not available
Paint	Orange, polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultra violet discoloration. All parts painted separately.	Orange, polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultra violet discoloration. All parts painted separately.	Orange, polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultra violet discoloration. All parts painted separately.	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	Specifications not available	N/A	Specifications not available	Specifications not available	Specification s not available

Manufacturer Model	Salsco 86 Series	Salsco 6235B	Salsco 6235BXT	Wallenstein BTX4224	Wallenstein BXT6224/38	Wallenstein CR 60	Bear Cat CH6670H	Bear Cat CH6614	Bear Cat CH6730H	Brush Bandit 65XP	Rayco RC 6D	Vermeer BC600XL	Carlton 660
Options	Speed Sensing, Spare tire and rim, Custom paint	N/A	Speed Sensing	Power Pack	Power Pack	Specifications not available	Chipper blade kits	Feed Sensing	Chipper blade kits	Spare tire and wheel, Reversing Auto Feed, Lockable fuel and hydraulic tank, Special paint colors, Knife Saver knife, sharpener, Hand crank swivel discharge, Height adjustable discharge (hand crank), Engine top cover for air-cooled engines, Dual feed wheels, 303CR rubber track undercarriage, w/ radio remote	Specifications not available	Special paint, extended warranty, preventive maintenance	Specifications not available
Dimensions	109" X 78" X 90"	132" X 66" X 79"	132" X 66" X 79"	74" X 88" X 88"	74" X 88" X 88"	116" X 62" X 96"	105" X 58" X 97"	76" X 80" X 90"	105" X 58" X 97"	67" X 91" X 122"	102" X 94" X 52.5"	110" X 53.5" X 94"	87" X 56"
Weight	2,120 LBS.	1,490 LBS.	1,640 LBS.	1365 LBS.	1385 LBS.	2,225 LBS.	1,850 LBS.	1,445 LBS.	1,635 LBS.	1,850-lbs. (gas engines) 2,700-lbs. (diesel engines)	1,960 lbs.	2,120 lbs.	1600 lbs.
Warranty	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	2 Year Homeowner 1 Year Commercial	2 Year Homeowner 1 Year Commercial	2 Year Homeowner 1 Year Commercial	1 Year		1-Year/1000-hour limited warranty	