

CHIPPER - 62 SERIES

6" Capacity Hydraulic Feed

Salsco, INC.
LEADER BY DESIGN



**MADE IN
THE U.S.A.**



The Model 62 Series hydraulic feed chippers are **6" round wood capacity chippers with dual feed Rolls**. Engine options include Honda, or Briggs & Stratton gas engines. The Torflex Axle provides a smooth, quiet ride and features an independent suspension. Full LED light package is standard and DOT approved. Rear lights are enclosed and mounted to heavy duty, 1/4" thick diamond plate fenders. Other standard features include an engine debris guard, easy adjustable 360° exhaust chute & chip deflector, both of which are easily adjusted without the use of tools. **Speed Sensing** is available as an option.

Dual Feed Rolls - Hydraulic Feed

The impeller housing opens easily for access to the chip blades and is equipped with a **Safety Switch Feature**. The engine will not start if the impeller housing is not closed and securely pinned.



Safety Switch



Infeed opening is **7" High x 8" Wide**. Extra wide infeed tray opens up to a full 49" from the infeed rolls.

The 62 series hydraulic feed chippers protect themselves against the operator! When the operator starts up the engine, if the impeller doesn't begin to turn within 15 seconds, the engine stops to warn the operator of a problem. If the impeller doesn't come up to full R.P.M., it won't feed.



Bed Knife

The **Bed Knife** is adjustable, sharpenable, and reversible.



E-Stops

Dual Emergency Stop Buttons are easily accessible from either side of the infeed tray. The **Forward/Neutral/Reverse Infeed Control Bar** is also easily accessed from either side of the infeed tray.

Salsco, INC.
LEADER BY DESIGN

Quality of Workmanship, Innovative Design, Built to Last!

SPECIFICATIONS - 62 Series Hydraulic Feed	
ENGINE OPTIONS:	24HP Honda; 35HP Briggs & Stratton; gas, electric start.
FUEL TANK:	6 gallon, CARB approved canister fuel tank.
BATTERY:	12 volt, CCA650, automotive type.
CLUTCH:	Centrifugal clutch, triple band cogged V-belt.
EXHAUST CHUTE:	360° swivel exhaust chute and exhaust flap are both quickly and easily adjusted to direct exhaust with no tools.
INFEED OPENING:	7" wide x 8" high at the infeed.
INFEED TRAY:	Extra wide, 24" wide x 29" high, 1/4" thick steel plate sides, with fold down infeed tray. Control bar positioned at top of infeed tray to control movement of the feed rolls. High speed, low speed, neutral & reverse & dual emergency stop buttons.
FEED ROLLS:	Two (2), 12" long x 5-1/2" diameter weighted feed rolls, replaceable blades, fully welded.
IMPELLER HOUSING:	1/4" thick steel, impeller housing is vented to provide more air flow for chip exhaust. Electric safety lock.
IMPELLER:	Fully balanced, 1" thick x 29" diameter steel impeller with six (6) welded and gusseted exhaust paddles. 210 lbs. (Approximately)
CHIP BLADES:	Six (6), 1/2" thick x 4" long x 4" wide, double-sided.
BED KNIFE:	1/2" thick steel, replaceable, sharpenable & adjustable.
BEARINGS:	4-bolt, heavy duty, cast iron, greaseable & self-centering.
HYDRAULIC COMPONENTS:	Hoses - SAE JIC hose ends & fittings. 3,000 P.S.I. working & 12,000 P.S.I. burst. Motors - Two (2), Char-Lynn 22.6 displacement. Pump - Hydro-Gear, variable speed.
HYDRAULIC TANK:	8-1/2" x 10" x 12" steel tank. 3.3 gallon capacity, with lockable filler cap with dip stick.
TRAILER FRAME & TONGUE:	7 gauge steel frame, fully welded and gusseted. Side-wind 2,000 lb. jack, 2" ball coupler with engine debris guard.
AXLE:	2,200 lb. Torflex Idler Axle, features an independent suspension, cushioned with rubber, providing a smooth, quiet ride with no transfer of road shock from one wheel to the other.
FENDERS/LIGHTS:	Extra heavy duty 1/4" thick diamond plate fenders with safety light guards. LED light package, D.O.T. approved.
TIRE/WHEEL ASSEMBLIES:	Two (2), ST205/75R14 LR "C". High speed, highway rim mounted on a 6-bolt white spoke wheel.
GUARDS/DECALS:	All moving parts guarded. Full set of safety decals.
PAINT:	Orange, polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultraviolet discoloration. All parts painted separately.
OPTIONS:	Speed Sensing
DIMENSIONS:	Length: 11' Width: 5' 6" Height: 6' 9" Weight: 1,600 lbs. (Approximately)

Specifications & Options Subject to Change Without Notice

REV. 10-29-2020

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawncare, Rental, Construction, Tree Care, Wood Processing, Nursery & Farm Industries
3-1/2" - 18" Capacity, Gas, Diesel, & PTO Wood/Brush Chippers - Slab Chippers
Gas, Electric & Tow Behind Rollers - Tranz-Former Roller - CRV Core Recovery Vehicle
Mini-Paver - Mini-Track Paver - Cobra Curbers - Scorpion Router - Concrete Paver
Chipper Shredder Vacuums - Tailgate & Truckloader Vacuums
9 cu. yds. - 50 cu. yds. Per Hour, Electric, PTO & Diesel Powered Shaving Mills

Salsco, INC.
 LEADER BY DESIGN

105 Schoolhouse Road
 Cheshire, CT 06410 U.S.A.
 800-872-5726 (Toll Free), 203-271-1682, 203-271-2596 (Fax)
www.salsco.com, sales@salsco.com