

## 4" CAPACITY COMPARISON

Manufacturer	Salsco	Salsco	Wallenstein	Bear Cat
Model	624PTO	824PTO	BX 42s	CH45540
Capacity	4 " Rd.wood cap. (max 5" slab)	4" Rd. wood cap. (max 8" slab)	4"	4 1/2"
HP Requirements	PTO Driven, 16HP minimum required at the PTO. Gravity Feed	PTO Driven, 15HP minimum required at the PTO. Hydraulic Feed (self contained hydraulics)	PTO Driven 16HP to 40HP required, Self feeding	PTO Driven 15HP to 28HP
Infeed Opening	4"H X 5"W	4"H X 8"W	4" X 10"	4 1/2" X 4 1/2"
Impeller Housing	7 gauge thick steel. Impeller housing is vented to provide more air flow for chip exhaust.	7 gauge thick steel. Impeller housing is vented to provide more air flow for chip exhaust.	Specifications not available	7 gauge chipper housing
Impeller	3/4" thick X 22-1/4" dia. Fully balanced, 4 exhaust paddles, welded & gusseted. 117 lbs.	3/4" thick X 18-7/8" dia. Fully balanced, 6 exhaust paddles welded & gusseted. 160 lbs.	25" Rotor 75 LBS.	14" 49 LBS.
Chipper Knives	(2) 1/2" thick x 7" long, double-sided.	(2) 1/2" thick x 7" long, double sided.	4 knives	2 Reversible
Bed Knives	(1) Replaceable, sharpenable, adjustable - 1/2" thick steel.	(2) One horizontal and one vertical. Replaceable, sharpenable, adjustable - 1" thick steel	1 bed knife	4 sided adjustable steel anvil
Exhaust Chute	360 degree swivel chute with adjustable chip deflector. No tools required for adjustment.	360 degree swivel chute with adjustable chip deflector. No tools required for adjustment.	60" Discharge Hood Height	Standard
Hitch	3 point hitch. iMatch bracket available.	3 point hitch	3 point hitch mount iMatch & quick hitch compatible	3 point hook up
Options		Speed sensing, skid steer adapter plate	Specifications not available	Specifications not available
Dimensions	55" X 48" X 70"	29" X 64" X 69"	32" X 42" X 65"	40" X 37" X 43"
Weight	525 LBS.	675 LBS.	425 LBS.	361 LBS.
Warranty	1 Year	1 Year	1 Year	1 year Commercial 2 Years Homeowner