

# CHIPPER Model 627XT, PTO



The Model 627XT, PTO is a **6" capacity hydraulic feed chipper** with a large 7" x 8" infeed opening to **dual feed rolls**. This unit utilizes **(6) 1/2" thick x 5-1/8" long x 4" wide, double-sided chip blades** and a 1/2" thick, reversible, sharpenable, and



replaceable bed knife for consistent chip size. 360° exhaust chute, and easy adjust exhaust flap. No tools are required to adjust either one. Dual infeed rolls and adjustable infeed speed help to prevent clogging & wrapping. **540 RPM recommended**. Bolted swing away infeed allows easy access to feed rolls.

## Only 25HP Required @ the PTO!

**7" x 8" infeed opening to dual infeed rolls.** Extra wide fold down infeed pan, is 75" from infeed rolls to edge of pan. The infeed handle is easily accessible



from either side of the unit, and has a full reverse, neutral, slow and fast speed. **Fully balanced 1" thick x 29" diameter 210 lb. impeller.**



Optional Speed Sensing (pictured to the left) automatically monitors

impeller RPM and stops infeed to allow RPM recovery. I-Match quick attach adapter (Pictured to the right) is available as an option.



<b>SPECIFICATIONS - MODEL 627XT, PTO CHIPPER</b>	
<b>INFEED OPENING:</b>	7" x 8" infeed opening to dual infeed rolls.
<b>INFEED TRAY:</b>	Extra wide, 23" wide x 25" high, with fold down infeed tray. Control bar positioned at top of infeed tray to control movement of the feed roll. High speed, low speed, neutral & reverse.
<b>FRAME:</b>	7 gauge steel frame, fully welded and gusseted for strength.
<b>IMPELLER HOUSING:</b>	7 gauge steel, impeller housing is vented to provide more air flow for chip exhaust.
<b>EXHAUST CHUTE:</b>	360° swivel exhaust chute and exhaust flap are both quickly and easily adjusted to direct exhaust with no tools.
<b>FEED ROLLS:</b>	Two (2), 12" long x 5-1/2" diameter, weighted, replaceable blades, fully welded.
<b>IMPELLER:</b>	Fully balanced, 1" thick x 29" diameter steel impeller with three (3) welded and gusseted exhaust paddles. 210 lbs. (Approximately)
<b>CHIP BLADES:</b>	Six (6), 1/2" thick x 5-1/8" long x 4" wide, double-sided.
<b>BED KNIFE:</b>	One (1), 1/2" thick steel, replaceable, sharpenable & adjustable.
<b>DRIVE SHAFT &amp; SHIELD:</b>	Drive shaft with shield, rated at 35HP @ 540 RPM.
<b>HITCH:</b>	3-Point Hitch, Category 1.
<b>BEARINGS:</b>	4-bolt, heavy duty, cast iron, greaseable & self-centering.
<b>HYDRAULIC COMPONENTS:</b>	<b>Hoses</b> - SAE JIC hose ends & fittings. 3,000 P.S.I. working & 12,000 P.S.I. burst. <b>Motor</b> - 23.8 displacement for easy connection to tractor remotes. <b>Flow control</b> is standard.
<b>GUARDS/DECALS:</b>	All moving parts guarded. Full set of safety decals.
<b>PAINT:</b>	Orange, polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultraviolet discoloration. All parts painted separately.
<b>OPTIONS:</b>	Speed Sensing; I-Match Quick Attach Adapter.
<b>DIMENSIONS:</b>	Length: 6' 2"
	Width: 5' 7"
	Height: 6' 10"
	Weight: 1,324 lbs.

Specifications & Options Subject to Change Without Notice

REV. 3-27-2020

#### MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawn care, Rental, Construction, Tree Care, Wood Processing, Nursery & Farm Industries

**3-1/2" - 18" Capacity, Gas, Diesel, & P.T.O. Wood/Brush Chippers**

**Gas & Electric Rollers - Tranz-Former - CRV Core Recovery Vehicle**

**Mini-Paver - Mini-Track Paver - Cobra Curber - Scorpion Router - Concrete Paver**

**Chipper Shredder Vacuums - Tailgate & Truckloader Vacuums**

**9 cu. yds. - 50 cu. yds. Per Hour, Electric, P.T.O. & Diesel Powered Shaving Mills**

105 School House Road

Cheshire, CT 06410 U.S.A.

800-872-5726 (Toll Free), 203-271-1682, 203-271-2596 (Fax)

[www.salsco.com](http://www.salsco.com), [sales@salsco.com](mailto:sales@salsco.com)

***Salsco***, INC.  
LEADER BY DESIGN