

6" CAPACITY COMPARISON

Manufacturer	Salsco	Salsco	Salsco	Wallenstein	Bear Cat	Brush Bandit
Model	627PTO	627XT	826 PTO	BX62s	CH4540	65XL
Capacity	6" Rd. wood cap. (max 8" slab)	6" Rd. wood cap. (max 8" slab)	6" Rd. wood cap. (max 12" slab)	6"	6"	6"
HP Requirements	PTO Driven, 25HP minimum required at the PTO. Gravity Feed	PTO Driven, 25 HP minimum required at the PTO. Hydraulic Feed	PTO Driven, 25HP minimum required at the PTO. Hydraulic Feed (self contained hydraulics)	PTO Driven 35HP to 40HP	PTO Driven, 25HP to 45HP required, Gravity Feed	PTO Driven 20HP TO -45HP
Infeed Opening	7"H X 8"W	7"H X 8" W	6"H X 12"W	6 1/2" X 12"	5.5 " X 7 "	6" X 12"
Impeller Housing	7 gauge thick steel. Impeller housing is vented to provide more air flow for chip exhaust.	7 gauge thick steel. Impeller housing is vented to provide more air flow for chip exhaust.	7 gauge thick steel. Impeller housing is vented to provide more air flow for chip exhaust.	Specifications Not Available	Specifications Not Available	Specifications not available
Impeller	1" thick X 29" dia. Fully balanced, 6 exhaust paddles welded & gusseted. 210 lbs.	1" thick x 29" dia. Fully balanced, 6 exhaust paddles welded & gusseted. 210 lbs.	1" thick X 26" dia. Fully balanced, 6 exhaust paddles welded & gusseted. 200 lbs.	23" Rotor	20" x 1.25"nch, 140 LBS.	26" diameter X 3/4" thick
Chipper Knives	(6) 1/2" thick x 4" long, double-sided.	(6) 1/2" thick x 4" long, double-sided.	(4) 1/2" thick x 4" long, double sided.	4 knives	4 reversible chipper blades	7 1/4" X 4" X 1/2"
Bed Knives	(1) Replaceable, sharpenable, adjustable - 1/2" thick steel	(1) Replaceable, sharpenable, adjustable - 1/2" thick steel.	(2) One horizontal and one vertical Replaceable, sharpenable, adjustable - 1" thick steel	1 bed knife	Specifications Not Available	2 pocket, 1/4" chip, 80FPM (1 knife per pocket)
Exhaust Chute	360 degree swivel chute with adjustable chip deflector. No tools required for adjustment.	360 degree swivel chute with adjustable chip deflector. No tools required for adjustment.	360 degree swivel chute with adjustable chip deflector. No tools required for adjustment.	74" Discharge Hood Height	360 degree rotating 6" discharge chute	360 degree manual swivel & adjustable deflector
Hitch	3 point hitch. iMatch bracket available	3 point hitch. iMatch bracket available	3 point hitch	3 point hitch mount iMatch & quick hitch compatible	3-point hook up	3-point hitch
Options	Speed Sensing	Speed Sensing	Speed sensing, skid steer adapter plate	Specifications Not Available	Specifications Not Available	6-tooth & 21-tooth spline adaptor to connect to PTO shaft, slip clutch for PTO Drive
Dimensions	64" X 64" X 86"	64" X 64" X 86"	65" X 52" X 84"	50" X 52" X 74"	40" X 37" X 43"	
Weight	955 LBS.	955 LBS.	1560 LBS.	770 LBS.	600 LBS.	1550 LBS.
Warranty	1 Year	1 Year	1 Year	1 Year	1 year Commercial 2 Years Homeowner	1 Year