

CHIPPER

Model 826PTO



The 826PTO has a **6" high x 12" extra wide infeed opening** to accommodate brushy material, and an extra long infeed tray for safety. The infeed tray folds up for ease of storage and transportation. Minimum horsepower is 25HP at the PTO and only **requires 540 RPM**. Hydraulics are self-contained; no remote connections to the tractor are needed. The control handle is easily accessed from either side and has a slow speed, high speed, neutral and reverse.



The Skid Steer Plate, complete with all necessary hydraulics is available as an option and can be used with either high or low flow.

Only 25HP Required at the PTO!



The Speed Sensing option counts the impeller RPM and when the impeller slows down, the speed sensing kicks in and stops the feed roll until it picks up the proper RPM for maximum efficient operation.



The **200 lb. impeller is 26" in diameter and 1" thick steel**. It has 6 welded and gusseted exhaust blades to exhaust chips, and **4 reversible 1/2" thick blades**. Extra wide chip pockets decrease clogging by allowing for better air flow and chip exhaust.



The infeed opening on the 826PTO is 6" high x 12" wide. This extra wide opening accommodates brushy material as well as 6" round branches, greatly reducing pruning and trimming of material.

SPECIFICATIONS - MODEL 826PTO

INFEED OPENING:	6" high x 12" wide opening at the infeed.
INFEED TRAY:	Extra wide, 40" wide x 23" high, with fold down infeed tray. Control bar positioned at top of infeed tray to control movement of the feed roll. High speed, low speed, neutral & reverse.
FRAME & ADJUSTABLE LEGS:	Frame - 2" x 3" x 1/4" wall. Legs Frame - 2-1/2" X 2-1/2" x 3/16" wall. Legs - 2" x 2" x 1/4" wall.
IMPELLER HOUSING:	1/4" thick steel, impeller housing is vented to provide more air flow for chip exhaust.
EXHAUST CHUTE:	360° swivel exhaust chute and exhaust flap are both quickly and easily adjusted to direct exhaust with no tools.
FEED ROLL:	One (1), 7" long x 12" diameter, weighted, replaceable blades, fully welded.
IMPELLER:	Fully balanced, 1" thick x 26" diameter steel impeller with six (6) welded and gusseted exhaust paddles. 200 lbs. (Approximately)
CHIP BLADES:	Four (4), 1/2" thick x 5-1/8" long x 4" wide, double-sided.
BED KNIVES:	Two (2), one horizontal, one vertical. Both are 1" thick steel, reeplaceable, sharpenable & adjustable.
DRIVE SHAFT & SHIELD:	Drive shaft with shield, rated at 47HP @ 540RPM.
HITCH:	3-Point Hitch, Category 2.
BEARINGS:	4-bolt, heavy duty, cast iron, greaseable & self-centering.
HYDRAULIC COMPONENTS:	Hoses - SAE JIC hose ends & fittings. 3,000 P.S.I. working & 12,000 P.S.I. burst. Motor - Char-Lynn 17.9 displacement. Pump - Hydro-Gear, variable speed.
GUARDS/DECALS:	All moving parts guarded. Full set of safety decals.
PAINT:	Orange, polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultraviolet discoloration. All parts painted separately.
OPTIONS:	Skid Steer Adapter Plate; Speed Sensing.
DIMENSIONS:	Length: 5' 5"
	Width: 4' 4"
	Height: 7'
	Weight: 1,560 lbs.

Specifications & Options Subject to Change Without Notice.

REV. 11-3-2020

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawn care, Rental, Construction, Tree Care, Wood Processing, Nursery & Farm Industries

3-1/2" - 18" Capacity, Gas, Diesel, & PTO Wood/Brush Chippers - Slab Chippers
Gas, Electric & Tow Behind Rollers - Tranz-Former Roller - CRV Core Recovery Vehicle
Mini-Paver - Mini-Track Paver - Cobra Curbers - Scorpion Router - Concrete Paver
Chipper Shredder Vacuums - Tailgate & Truckloader Vacuums
9 cu. yds. - 50 cu. yds. Per Hour, Electric, PTO & Diesel Powered Shaving Mills

Salsco, INC.

LEADER BY DESIGN

105 Schoolhouse Road
 Cheshire, CT 06410 U.S.A.
 800-872-5726 (Toll Free), 203-271-1682, 203-271-2596 (Fax)
www.salsco.com, sales@salsco.com