

GAS ROLLER Roll-N-Go, EHA

Salsco, INC.
LEADER BY DESIGN



**MADE IN
THE U.S.A.**



Unit pictured with the
Cross Contamination Prevention Kit



Drive to the green, raise the wheels, roll the green, lower the wheels and drive to the next green. Self-Contained, no trailer or utility vehicle needed.

The Name Says It All: Roll-N-Go!

- * Great for Fairways, Approaches & Tees as well as Greens
- * Steering Wheel, no Joystick, Easy to Operate
- * 35% More Productive than any Trailered Roller
- * Rolling Swath is 3'
- * Transport Width is 5'6"
- * Roll an Average Green in only Six Minutes
- * Firm up your Greens in Less Time
- * Free up Tow Vehicles



Cross Contamination Prevention Kit

not only prevents the spread of disease or insects when rolling multiple areas, grass clippings will not clump on the end of the rolls, eliminating clean up. When used after top dressing, sand will disperse evenly across the greens.



Pedal Extensions allow employees with shorter legs to remain fully seated, engaging the seat switch, while still being able to reach the pedals.



The optional Inner Spike-Air Kit, when used on the green, will gently spike the green to allow water and oxygen to penetrate through the crust to the roots of the plant.



The optional LED Light Kit for the Gas Rollers allows for rolling in the early morning hours, before tournament play.

Salsco, INC.
LEADER BY DESIGN

Quality of Workmanship, Innovative Design, Built to Last!

SPECIFICATIONS AND OPTIONS - ROLL-N-GO, EHA GAS ROLLER	
WARRANTY:	5 Year Limited Warranty
ENGINE:	13HP Honda, electric start, rubber mounted to reduce vibration.
FUEL TANK:	6 gallon, CARB approved canister fuel tank.
CONTROLS:	On/Off switch, choke & fuel. Raise/ Lower rocker switch for wheels.
HOUR METER:	Standard
BATTERY:	12 Volt, 300 CCA, automotive type.
ENGINE COOLING FAN:	Cooling fan - Standard
SEAT:	Molded cushion, arm rest seat with protective edge trim. Neutral safety switch & forward/reverse slide adjustment. Rubber mounted to reduce vibration.
STEERING SYSTEM:	Both rolls articulate and oscillate to smooth the surface without changing the undulations designed into the green.
STEERING WHEEL:	13-1/4" diameter, automotive type tilt steering wheel, hydraulic assist steering. 13-1 Ratio
MAIN FRAME:	2-1/2" x 2-1/2" x 1/8" steel square tube. Fully gusseted with continuous welds.
DRIVE ROLLS:	Two (2) oscillating steel rolls, both driven for positive traction. 1-1/4" roll mounting bearing. 10-3/4" diameter, 36" long with beveled ends. Rolls are machined to within two thousandths of an inch concentricity.
TRACTION DRIVE:	Hydraulic pump to two (2) hydrostats - 1 to each roll. Chain drive from hydraulic motors to rolls. #50 chain & sprockets.
CLIMBING TRACTION:	Up to 40°
BRAKES:	Parking brake
HYDRAULIC COMPONENTS:	Hoses: SAE JIC hose ends & fittings. 3,000 P.S.I. working & 12,000 P.S.I. burst. Motors: Two (2) Char-Lynn 7.3 cubic inch displacement Pump: One (1) Hydro-Gear, 0.97 cubic inch displacement.
ELECTRIC HYDRAULIC CYLINDERS:	Four (4) double action, 6 stroke.
ROLLING SWATH:	36"
SPEED:	Variable, 0 - 11 MPH
GROUND PRESSURE:	10.2 P.S.I. without water, 11.6 P.S.I. with water.
TIRE/WHEEL ASSEMBLIES:	Four (4) 18.5 x 8.5-8, 6 ply, turf tires hydraulically operated. Two are drive wheels.
GUARDS/DECALS:	All moving parts guarded. Full set of safety decals.
PAINT:	Orange, polyester powder coat paint provides excellent outdoor weatherability and offers protection against ultraviolet discoloration. All parts painted separately.
ROLLER OPTIONS:	Cross Contamination Prevention Kit, LED Light Kit, Top Dressing Brush Kit, Inner Spike-Air Kit. Pedal Extensions.
TRANSPORT DIMENSIONS:	Length: 6'6" Width: 5'6" Height: 4'9" Weight: 1480 lbs.
ROLLING DIMENSIONS:	Length: 6'6" Width: 5'6" Height: 4'6" Weight: 1480 lbs.

Specifications & Options Subject to Change Without Notice

Rev. 9/10/2021

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawncare, Rental, Construction, Tree Care, Wood Processing, Nursery & Farm Industries

3-1/2" - 18" Capacity, Gas, Diesel, & PTO Wood/Brush Chippers - Slab Chippers
Gas, Electric & Tow Behind Rollers - Tranz-Former Roller - CRV Core Recovery Vehicle
Mini-Paver - Mini-Track Paver - Cobra Curbers - Scorpion Router - Concrete Paver
Chipper Shredder Vacuums - Tailgate & Truckloader Vacuums
9 cu. yds. - 50 cu. yds. Per Hour, Electric, PTO & Diesel Powered Shaving Mills

Salsco, INC.
 LEADER BY DESIGN

105 Schoolhouse Road
 Cheshire, CT 06410 U.S.A.
 800-872-5726 (Toll Free), 203-271-1682, 203-271-2596 (Fax)
www.salsco.com, sales@salsco.com