

GUIDANCE CONTROL CONCRETE PAVER TPC-72

Salsco, INC.
LEADER BY DESIGN



**MADE IN
THE U.S.A.**



The hopper is constructed of **Reinforced 1/4" Steel Plates** which are 100% continuously welded for strength and has a **1.5 Cubic Yard Capacity**. The hopper & screed assembly can be raised for easy loading onto trailer ramps. Hoppers come in different widths to match the screed of choice. Conveyor can be easily mounted to the unit on either side. Pictured below is the unit in transport position.



Rubber tracks have **Eight Idler Rolls** and a **Top Drive Sprocket** for smooth travel. Easy track

adjustment is obtained with the top sprocket. There are two hydrostatic pumps with electric actuators, one for each track drive. The pumps send power to the six to one gear reducer drives, resulting in **Continuous Power To The Tracks.**



Adjustable String Line Sensors

send information to the guidance control string line for screed height and steering. Vibrator is mounted to the top plate of the screed.



The Model TPC-72 is operated via a **Radio Controlled Belly Pack** instrument box, carried by the operator. The TPC-72 can be operated in manual or in full

automatic mode. In the auto mode, the machine will follow the guidance string and adjust tracking and screed elevation automatically. In the auto mode the operator could manually adjust travel speed.



4.3" Color Display with intuitive interface and many features such as **Engine Monitoring, Tracking & Elevation Calibration.**

Salsco, INC.
LEADER BY DESIGN

Quality of Workmanship, Innovative Design, Built to Last!

SPECIFICATIONS - GUIDANCE CONTROL CONCRETE PAVER "TPC-72"

ENGINE:	Hatz, Tier IV, 74HP Diesel Engine EPA compliant nationwide.
TRACKS:	Steel reinforced rubber tracks with eight idler rolls for support.
HOPPER:	1.5 Cu.Yd. Capacity. 1/4" Steel, 100% continuous welds.
SCREED:	Screeds come in different widths.
SCREED VIBRATOR:	Mounted to the top plate of the screed.
FUEL TANK:	1-fuel tank connected for a total of 35 gallons. Fuel consumption = 2 G.P.H.
HYDRAULIC TANK:	Hydraulic tank capacity is 33 gallons.
ELECTRICAL BOX:	Nema type weather proof box. Lockable. All harnesses unplug for easy service and replacement.
PUMPS:	1-20 GPM gear pump for all accessories. 2 - Poclain hydrostatic pumps with electric actuators for the track drives.
DRIVE MOTORS:	2 - Delta series 28.7 Cu.In. with electric actuators for remote controls.
BATTERY:	12-Volt, 850 CCA
CONTROLS:	Wireless remote and/or manual.
GUIDANCE CONTROL:	Moba guidance sensing controls.
CONVEYOR FEED:	15" wide, variable speed conveyor can be mounted on either side of the unit. Folds for transportation & cleaning.

Specifications & Options Subject to Change Without Notice

Rev. 5/25/2021

Other Curbing & Paving Equipment Manufactured by Salsco, Inc.



Mini-Track Asphalt Paver, TP44-TD



Side Dump Bucket



Scorpion Pavement Router



Under The Rail Concrete/Asphalt Curber

MANUFACTURER OF OUTDOOR POWER EQUIPMENT

Products for Turf & Lawn care, Rental, Construction, Tree Care, Wood Processing, Nursery & Farm Industries

3-1/2" - 18" Capacity, Gas, Diesel, & PTO Wood/Brush Chippers - Slab Chippers
Gas, Electric & Tow Behind Rollers - Tranz-Former Roller - CRV Core Recovery Vehicle
Mini-Paver - Mini-Track Paver - Cobra Curbers - Scorpion Router - Concrete Paver
Chipper Shredder Vacuums - Tailgate & Truckloader Vacuums
9 cu. yds. - 50 cu. yds. Per Hour, Electric, PTO & Diesel Powered Shaving Mills

Salsco, INC.
 LEADER BY DESIGN

105 Schoolhouse Road
 Cheshire, CT 06410 U.S.A.
 800-872-5726 (Toll Free), 203-271-1682, 203-271-2596 (Fax)
www.salsco.com, sales@salsco.com